



MADAME CURIESTRAAT 1, 2171 TW  
 SASSENHEIM, NETHERLANDS  
 INFO@MB-DUSTCONTROL.COM  
 WWW.SPRAYCANNON.COM  
 T. 0031(0)252-794010

# SPRAYCANNON 35

WWW.SPRAYCANNON.COM

## TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	20-35 (windstill cond.)
Surface (m <sup>2</sup> )	3400
Quantity of Nozzles	16
Water Usage (l/h)	1-1000
Fan (kW)	2,2
Pump (kW)	1,5
Working Pressure (Bar)	40
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Electricity	110/230V
Socket	16A
Supply Connection	1"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	1300x900x1300
Weight (kg.)	230



## AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control
- ✓ UV-installation
- ✓ Wheel Set
- ✓ Skid-mounted including generator
- ✓ Self-Supporting including water bowser and generator

### APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.

**WE BEAT ODOUR AND DUST!**