

SPRAYCANNON 25



MADAME CURIESTRAAT 1, 2171 TW
SASSENHEIM, NETHERLANDS
INFO@MB-DUSTCONTROL.COM
WWW.SPRAYCANNON.COM
T. 0031(0)252-794010

WWW.SPRAYCANNON.COM

TECHNICAL SPECIFICATIONS

Usage	Indoor/Outdoor
Distance (m)	15-25 (windstill cond.)
Surface (m ²)	70
Quantity of Nozzles	12
Water Usage (l/h)	1-300
Fan (kW)	1,5
Pump (kW)	0,75
Working Pressure (Bar)	40
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	No
Electricity	110/230V
Socket	16A
Supply Connection	1"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	950x800x1100
Weight (kg.)	100



APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.

AVAILABLE OPTIONS

✓ Fan Speed regulation

WE BEAT ODOUR AND DUST!