



MADAME CURIESTRAAT 1, 2171 TW
 SASSENHEIM, NETHERLANDS
 INFO@MB-DUSTCONTROL.COM
 WWW.SPRAYCANNON.COM
 T. 0031(0)252-794010

SPRAYCANNON 75

WWW.SPRAYCANNON.COM

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	50-75 (windstill cond.)
Surface (m ²)	15.000
Quantity of Nozzles	34
Water Usage (l/h)	500-3.500/4.500
Fan (kW)	18,5
Pump (kW)	4/5,5
Working Pressure (Bar)	20-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Electricity	400V
Socket	63A
Supply Connection	2"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	1850x1400x2200
Weight (kg.)	650

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control
- ✓ UV-installation
- ✓ Wheel Set
- ✓ Skid-mounted including generator
- ✓ Self-Supporting including water bowser and generator

WE BEAT ODOUR AND DUST!